

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A method for exchanging shears (3) in the cutting to length of strips (1) or sheet metal in a rolling or transport line (x-x), ~~in particular,~~ on a rolling table (2), with blade holders (4, 4'), one arranged above and one arranged below the strip (1), which blade holders are guided by holding elements (5, 5'; 6, 6'), wherein the shears (3) can be moved together with the blade holders (4, 4') and with holding elements (5, 5'; 6, 6') for the blade holders after each cut out of the rolling line (x-x) to the side into a neutral waiting position, while the strip or sheet metal is in the rolling or transport line, and that, before moving out the shears (3), a forward connection between the blade holders (4, 4') or between the holding elements (6, 6') overlapping the rolling line (x-x) is opened, and that the shears (3) for a subsequent cut are

moved into the rolling line so as to overlap it in a U-shape, and that the forward connection is closed and, by employing a clamping element (7), is form-fit connected and frictionally connected before a subsequent cut, wherein, when moving the shears (3) into the rolling or transport line (x-x), a part (2') of the rolling table (2) is moved out of the rolling or transport line (x-x) to the side and, simultaneously with moving the shears (3) out of the rolling or transport line (x-x) into the waiting position, the part (2') of the rolling table is again moved into the rolling table.

2. (Currently amended) A device for exchanging shears (3) in the cutting to length of strips (1) or sheet metal in a rolling or transport line, ~~in particular,~~ on a rolling table (2), wherein the shears (3), inclusive of the drive apparatus (8), are arranged on a rail-guided drive carriage (9) which, while the strip or sheet metal is positioned in the rolling or transport line, is movable by means of a drive (10) transverse to the rolling or transport line (x-x), wherein the shears (3) comprise a U-shaped frame (20) open toward the rolling or transport line (x-x) and closed at a drive side, on which, at the drive side as well as a rolling table side which is opposite the drive side, holding elements (5, 5'; 6,

6') are provided that support ~~the~~ blade holders (4, 4'), and wherein the drive carriage (9) is coupled with a movable part (2') of the rolling table (2).

3. (Previously presented) A device according to claim 2, wherein the drive carriage (9) at the rolling table side receives at least one clamping element (7) with actuating members (11, 25, 36).
4. (Previously presented) A device according to claim 2, wherein the U-shaped open side of the frame (20) has correlated therewith a clamping element (7) coupled with the holding element (6, 6') at the rolling table side.
5. (Previously presented) A device according to claim 2, wherein the clamping element (7) is provided with coupling elements (21) that couple with the holding elements (6, 6') of the frame arms (22, 29).
6. (Currently amended) A device for exchanging shears (3) in the cutting to length of strips (1) or sheet metal in a rolling or transport line on a rolling table (2), wherein the shears (3), inclusive of the drive apparatus (8), are

arranged on a rail-guided drive carriage (9) which, while the strip or sheet metal is positioned in the rolling or transport line, is movable by means of a drive (10) transverse to the rolling or transport line (x-x), wherein the shears (3) comprise a U-shaped frame (20) open toward the rolling or transport line (x-x) and closed at a drive side, on which, at the drive side as well as a rolling table side which is opposite the drive side, holding elements (5, 5'; 6, 6') are provided that support blade holders (4, 4'), and wherein the drive carriage (9) is coupled with a movable part (2') of the rolling table (2) ~~according to claim 2~~, wherein the holding element (6) at a free end of an upper, horizontal frame arm (22) comprises at least one pressure plate (23, 23') and the clamping element (7) has congruent gliding plates (24, 24' and 26, 26') for overlapping them, and that the clamping element (7) is movable by force means (25, 25') on a horizontal gliding path (38, 38') with its gliding plates (24, 24' and 26, 26') across the pressure plates (23, 23' and 37, 37) for generating a form-fit coupling and a frictional coupling.

7. (Currently amended) A device for exchanging shears (3) in the cutting to length of strips (1) or sheet metal in a rolling

or transport line on a rolling table (2), wherein the shears
(3), inclusive of the drive apparatus (8), are arranged on a
rail-guided drive carriage (9) which, while the strip or
sheet metal is positioned in the rolling or transport line,
is movable by means of a drive (10) transverse to the rolling
or transport line (x-x), wherein the shears (3) comprise a
U-shaped frame (20) open toward the rolling or transport line
(x-x) and closed at a drive side, on which, at the drive side
as well as a rolling table side which is opposite the drive
side, holding elements (5, 5'; 6, 6') are provided that
support blade holders (4, 4'), and wherein the drive carriage
(9) is coupled with a movable part (2') of the rolling table
(2) according to claim 2, wherein the holding element (6,6')
at the free end of the upper horizontal frame arm (22) is
provided with threaded spindle coupling rods (32, 32')
connected so as to be pivotable to both sides, which, by
means of recesses (27, 27'), are engageable in congruent
coupling sockets (28, 28') of the lower frame arm (29) or in
the congruent coupling sockets (28, 28') of the upper holding
element (6) and adjustable by a force means (30) for
generating a form-fit and frictional connection with the aid
of their spindle drives (31, 31').

8. (Currently amended) A device for exchanging shears (3) in the cutting to length of strips (1) or sheet metal in a rolling or transport line on a rolling table (2), wherein the shears (3), inclusive of the drive apparatus (8), are arranged on a rail-guided drive carriage (9) which, while the strip or sheet metal is positioned in the rolling or transport line, is movable by means of a drive (10) transverse to the rolling or transport line (x-x), wherein the shears (3) comprise a U-shaped frame (20) open toward the rolling or transport line (x-x) and closed at a drive side, on which, at the drive side as well as a rolling table side which is opposite the drive side, holding elements (5, 5'; 6, 6') are provided that support blade holders (4, 4'), and wherein the drive carriage (9) is coupled with a movable part (2') of the rolling table (2) ~~according to claim 2~~, wherein the clamping element (7) correlated transversely to the frame arms (22, 29) can be folded upwardly by means of a joint (34) with a pivot axis (35) extending parallel to the rolling line with the aid of at least one force means (36) for coupling of the two frame arms (22, 29) or folded down for releasing the coupling of the frame arms.